

ST5015UX-2H-US

ST5015UX-4H-US

PowerTitan 2.0 Liquid Cooled Energy Storage System

NEW



OPTIMAL COST

- Intelligent liquid-cooled temperature control system to optimize the auxiliary power consumption
- Pre-assembled, no battery module handling on site, transportation of complete system



SAFE AND RELIABLE

- Electrical safety management, overcurrent fast breaking and arc extinguishing protection
- The electrical cabinet and battery cabinet are separated to prevent thermal runaway



EFFICIENT AND FLEXIBLE

- High-efficiency heat dissipation, increase battery life and system discharge capacity
- Front single-door-open design, supporting back to back layout drawing
- Function test in factory, limited on-site work, accelerate commissioning process



CONVENIENT O&M

- One-click system upgrade
- Automatic coolant refilling design
- Online intelligent monitoring



Product name	ST5015UX-2H-US	ST5015UX-4H-US
DC side		
Cell type	LFP 3.2 V / 314 Ah	
Battery configuration	416S12P	
Nominal capacity	5015 kWh	
Nominal voltage range	1123.2 V ~ 1497.6 V	
AC side		
Nominal AC power	210 kVA * 12	210 kVA * 6
AC current distortion rate	< 3 % (Nominal Power)	
DC component	< 0.5 %	
Nominal AC voltage	690 V	
AC voltage range	607 V ~ 759 V	
Termination (LV)	352 A * 3 Phase * 6	352 A * 3 Phase * 3
Power factor	> 0.99 (Nominal Power)	
Adjustable range of reactive power	- 100 % ~ 100 %	
Nominal frequency	60 Hz	
Isolation method	Transformerless	
System parameter		
Dimension (W * H * D)	6058 mm * 2896 mm * 2438 mm 238.5" * 114.0" * 96.0"	
Weight	42500 kg / 93696.5 lbs	42000 kg / 92594.0 lbs
Degree of protection	Type 3S	
Anti-corrosion degree	C4	
Operation temperature range	- 30 °C ~ 50 °C (> 45 °C Derating) -22 °F ~ 122 °F (> 113 °F Derating)	
Operation humidity range	0 % ~ 100 %	
Max. operation altitude	3000 m / 9842.5 ft	
Temperature control method	Intelligent Liquid Cooling	
Fire suppression system	Default: NFPA 68 compliance vent panel, smoke and heat, detectors, Mini FACP Optional: Sprinkler, sound beacon, NFPA 69, compliance ventilation system, Flammable gas detector	
Communication	Ethernet	
Standard	UL 9540A, NFPA 855, NFPA 68, NFPA 69 (optional) IEEE 1547, UL 1973, UL 1741SB, UL 9540	

