

SG3300UD/SG4400UD PV Inverter for 1500Vdc System



HIGH YIELD

- Advanced three-level technology, max. inverter efficiency 99 %
- Effective cooling, full power operation at 45 °C



SMART O&M

- Integrated zone monitoring function for online analysis and trouble shooting
- Modular design, easy for maintenance



SAVED INVESTMENT

- Low transportation and installation cost due to outdoor design
- DC 1500 V system, low system cost
- Q at night function optional



GRID SUPPORT

- Compliance with standards: IEC 61727, IEC 62116
- Low / High voltage ride through (L/HVRT)
- Active & reactive power control and power ramp rate control



Type designation	SG3300UD	SG4400UD
Input (DC)		
Max. PV input voltage	1500 V	
Min. PV input voltage / Startup input voltage	895 V / 905 V	
MPP voltage range	895 V – 1500 V	
No. of independent MPP inputs	3	4
No. of DC inputs	15 (optional: 21)	20 (optional: 28)
Max. PV input current	3 * 1435 A	4 * 1435 A
Max. DC short-circuit current	3 * 3528 A	4 * 3528 A
PV array configuration	Negative grounding or floating	
Output (AC)		
AC output power	3300 kVA @ 45 °C	4400 kVA @ 45 °C
	3399 kVA @ 40 °C	4532 kVA @ 40 °C
	3795 kVA @ 22.5 °C	5060 kVA @ 22.5 °C
Max. AC output current	3 * 1160 A	4 * 1160 A
Nominal AC voltage	630 V	
AC voltage range	536 V – 693 V	
Nominal grid frequency / Grid frequency range	50 Hz / 45 Hz – 55 Hz, 60 Hz / 55 Hz – 65 Hz	
Harmonic (THD)	< 1.5 % (at nominal power)	
Power factor at nominal power / Adjustable power factor	> 0.99 / 0.8 leading – 0.8 lagging	
Feed-in phases / AC connection	3 / 3	
Efficiency		
Max. efficiency / European efficiency	99.0 % / 98.8 %	
Protection & Function		
DC input protection	Load break switch + fuse	
AC output protection	Circuit breaker	
Overvoltage protection	DC Type II / AC Type II	
Grid monitoring / Ground fault monitoring	Yes / Yes	
Insulation monitoring	Yes	
Surge protection	Yes	
Q at night function	Optional	
General data		
Dimensions (W*H*D)	2340 mm * 2300 mm * 1550 mm	2900 mm * 2300 mm * 1550 mm
Weight	2.5 T	3.3 T
Topology	Transformerless	
Degree of protection	IP65	
Night power consumption	< 200 W	
Operating ambient temperature range *	-35 °C - 60 °C	
Allowable relative humidity range	0 % – 100 %	
Cooling method	Temperature controlled forced air cooling	
Max. operating altitude	4000 m (> 3000 m derating)	
Display	LED Indicators, Ethernet+WebHMI	
Communication	Standard: RS485, Ethernet	
Compliance	CE, IEC 62109, IEC 61727, IEC 62116, IEC 60068, IEC 61683, VDE-AR-N 4110:2018, VDE-AR-N 4120:2018, EN 50549-2, UNE 206007-1:2013, NTS 631, UTE C15-712-1:2013	

* The ambient temperature is determined as the average temperature obtained from at least four temperature monitoring points located at a distance of 1 meter from the equipment, at a height halfway up the machine. The temperature sensors must be shielded from airflow, thermal radiation, and rapid temperature fluctuations to prevent display inaccuracies.

EFFICIENCY CURVE

