

## MG5RL / MG6RL

NEW



### Robust Power Performance

- 100% full power backup output, delivering stable performance even at temperatures above 45°C
- Whole-home backup with 40 A bypass switch



### Robust Backup Power

- 4ms Seamless Switch<sup>1)</sup>
- 10 seconds of 200% backup peak power capability



### Robust Solar Generation

- Industry-leading Max. 20A PV input per string
- Wider MPPT voltage range



### Robust Safety Features

- Dual-system pressure relief structure



### Robust Control Interface

- 4.3-inch large LCD touchscreen
- Multi-functional interface for Generator, Smart load control or Sungrow string inverter



Technical Data Sheet	MG5RL	MG6RL
<b>Input (DC)</b>		
Recommended max. PV input power	10000 Wp	12000 Wp
Max. usable PV input power	8000 Wp	9600 Wp
Max. PV input voltage	500 V	
Min. PV input voltage / Startup input voltage	40 V / 50 V	
Rated PV input voltage	360 V	
MPPT operating voltage range <sup>2)</sup>	40 V – 425 V	
No. of independent MPP trackers	2	
No. of PV strings per MPPT	1 / 1	
Max. PV input current	40 A ( 20 A / 20 A )	
Max. DC short-circuit current	50 A ( 25 A / 25 A )	
Max. current for DC connector	25 A	
<b>Battery data</b>		
Battery type	Li-ion battery / Lead-acid battery	
Compatible battery model	MGL060 / MBL050 / MBL120 / MBL160 / Third-party LV batteries	
Battery voltage range	40 V – 60 V	
Max. charge / discharge current <sup>3)</sup>	120 A / 120 A	135 A / 135 A
Max. charge / discharge power	5000 W / 5000 W	6000 W / 6000 W
<b>Input / Output (AC)</b>		
Max. AC power from grid	8800 W	
Rated AC output power	5000 W	6000 W
Max. AC output apparent power	5000 VA	6000 VA
Max. AC output current	22.7 A	27.3 A
Rated AC voltage	220 V / 230 V / 240 V	
AC voltage range	154 V – 276 V	
Rated grid frequency	50 Hz / 60 Hz	
Grid frequency range	45 Hz – 55 Hz / 55 Hz – 65 Hz	
Harmonic ( THD )	< 3% ( of rated power )	
Power factor at rated power / Adjustable power factor	> 0.99 at default value at rated power / 0.8 leading to 0.8 lagging	
Feed-in phases / Connection phases	1 / 1	
<b>Backup Data (on grid mode)</b>		
Max. output power for backup load <sup>4)</sup>	8800 W	
Max. output current for backup load	40 A	
<b>Backup Data (off-grid mode)</b>		
Rated voltage	220 V / 230 V / 240 V	
Rated frequency	50 Hz / 60 Hz	
THDV ( @ Linear load )	< 2 %	
Backup switch time	≤ 4 ms	
Rated output power	5000 W	6000 W
Max. output power for backup load	5500 W	6600 W
Peak output power	2 times of rated power, 10 s	
<b>Efficiency</b>		
Max. efficiency / European efficiency	97.6 % / 96.7 %	
<b>Protection &amp; Function</b>		
Grid monitoring	Yes	
DC reverse polarity protection	Yes	
AC short-circuit protection	Yes	
Leakage current protection	Yes	
DC switch ( solar )	Yes	
Surge protection	DC Type II / AC Type III	
PID Zero	Yes	
Micro-inverter compatibility <sup>5)</sup>	Optional	
Arc fault circuit interrupter ( AFCI )	Optional	
<b>General Data</b>		
Topology ( Inverter )	Non-isolated	
Topology ( Battery BDC )	Isolated	
Degree of protection	IP65	
Dimensions ( W * H * D )	532 mm * 386 mm * 210 mm	
Weight	< 19 kg	
Mounting method	Wall-mounting bracket	
Operating ambient temperature range	-25 °C to 60 °C	
Allowable relative humidity range	0 % – 95 %	
Cooling method	Natural convection	
Max. operating altitude	2000 m	
Noise ( typical )	≤ 35 dB ( A )	
Display	LCD digital touchable display & LED indicator	
Communication	CAN, RS485, Ethernet, WLAN	
DI / DO	DI * 1 / DO * 1	
DC connection type	MC4 compatible ( Max. 6 mm <sup>2</sup> )	
Battery connection type	OT terminal ( 35 mm <sup>2</sup> – 50 mm <sup>2</sup> )	
AC connection type	Plug and Play ( Max. 8 AWG )	
Scalability <sup>6)</sup>	8 in parallel	
Grid compliance	IEC 62109-1/-2, IEC/EN 61000-6-1/-3, IEC 62116, IEC 61727, NRS 097-2-1, MEA, PEA, DEWA	

<sup>1)</sup> Available in typical conditions

<sup>2)</sup> Please refer to the user manual for the full load MPPT voltage range

<sup>3)</sup> The system's charging and discharging capability is also limited by the battery's charging and discharging performance

<sup>4)</sup> Please refer to the user manual and modify the settings based on actual load power

<sup>5)</sup> For micro-inverter compatibility, it is only available for the grid-connection port of the inverter

<sup>6)</sup> If the number of inverters in parallel exceeds 4, please consult SUNGROW