

# ST2752UX-US

Liquid Cooled Battery Energy Storage System Container  
2 - 8 Hour Application



## LOW COSTS

- Highly integrated ESS for easy transportation and O&M
- All pre-assembled, no battery module handling on site
- 8 hour installation to commission, drop on a pad and make electrical connections



## SAFE AND RELIABLE

- Integrated DC/DC converters actively limit fault current
- DC electric circuit safety management includes fast breaking and anti-arc protection
- Multi level battery protection layers formed by discreet standalone systems offer impeccable safety



## EFFICIENT AND FLEXIBLE

- Intelligent liquid cooling ensures higher efficiency and longer battery cycle life
- Modular design supports parallel connection and easy system expansion
- IP54 outdoor cabinet and optional C5 anti-corrosion



## SMART AND ROBUST

- Fast state monitoring and faults record enables pre-alarm and faults location
- Integrated battery performance monitoring and logging



Type designation	ST2752UX-US
<b>Battery Data</b>	
Cell type	LFP
Battery capacity (BOL)	2752 kWh
Battery voltage range	1160 ~ 1500 V
<b>General Data</b>	
Dimensions of battery unit (W * H * D)	9340*2600*1730mm
Weight of battery unit	26,400kg
Degree of protection	IP 54/Type 3R
Operating temperature range	-30 to 50 °C (> 45 °C derating)
Relative humidity	0 ~ 95 % (non-condensing)
Max. working altitude	3000m
Cooling concept of battery chamber	Liquid cooling
Fire safety	Fused sprinkler heads, NFPA 69 explosion prevention and ventilation IDLH gases
Communication interfaces	RS485, Ethernet
Communication protocols	Modbus RTU, Modbus TCP
Compliance	UL 9540,UL 9540A/NFPA 855
<b>2 HOURS APPLICATION-ST2752UX*4-5000UD-MV-US</b>	
BOL kWh(DC/AC LV Side)	11,008kWh DC/10,379kWh AC
ST2752UX Quantity	4
PCS Model	SC5000UD-MV-US
<b>4 HOURS APPLICATION-ST2752UX*8-5000UD-MV-US</b>	
BOL kWh(DC/AC LV Side)	22,016kWh/21,448kWh
ST2752UX Quantity	8
PCS Model	SC5000UD-MV-US
<b>Grid Connection Data</b>	
Max.THD of current	< 3 % (at nominal power)
DC component	< 0.5 % (at nominal power)
Power factor	> 0.99 (at nominal power)
Adjustable power factor	1.0 leading ~ 1.0 lagging
Nominal grid frequency	60 Hz
Grid frequency range	55 ~ 65 Hz
<b>Transformer</b>	
Transformer rated power	5,000 kVA
LV/MV voltage	0.9 kV / 34.5 kV
Transformer cooling type	ONAN (Oil Natural Air Natural)
Oil type	Mineral oil (PCB free) or degradable oil on request