

SH110CX

Multi-MPPT Commercial & Industrial Hybrid Inverter



SUPERIOR YIELD

- Up to 200 % PV oversizing
- 40 A x 10 MPPTs with 182 / 210 mm high-power PV modules
- PID Zero[®] anti-PID technology



FLEXIBLE APPLICATION

- Smart trading ready for intelligent TOU, dynamic pricing, and VPP participation
- DC coupled solution for new installation and retrofit upgrades
- 100 % three-phase unbalance output



ROBUST PERFORMANCE

- 150 % off-grid overload (10 s)
- Up to 200 A charge / discharge current
- Built-in ≤ 10 ms UPS level on / off-grid switching



ACTIVE SAFETY

- AFCI 3.0, intelligent DC arc interrupter, with a detection range of 450 m
- Intelligent string-level protection switch & PV-to-Ground fault protection
- IP66, C5, and self-cleaning air ducts function



Type designation	SH110CX
Input (DC)	
Max. PV input power	220 kWp
Max. PV input voltage *	1100 V
Min. PV input voltage / Startup input voltage	180 V / 200 V
Rated PV input voltage	600 V
MPPT voltage range **	180 V - 1000 V
No. of independent MPP inputs	10
No. of PV strings per MPPT	2
Max. PV input current	40 A * 10
Max. DC short-circuit current	50 A * 10
Max. current for DC connector	30 A
Battery input data	
Battery type	Lithium-ion battery
Battery Voltage Range***	129 V - 880 V
Communication	CAN
Max. charge / discharge current****	200 A / 200 A
Max. charge / discharge power	110 kW / 110 kW
Input and output (AC)	
Max. AC power from grid	110 kVA @ 230 V
Rated AC output power	110 kW
Max. AC output apparent power	110 kVA
Max. AC output current	158.8 A
Rated AC output current	158.8 A
Rated AC voltage	3 / N / PE, 220 V / 380 V, 230 V / 400 V
AC voltage range	270 V - 480 V
Rated grid frequency	50 Hz / 60 Hz
Grid frequency range	45 Hz - 55 Hz / 55 Hz - 65 Hz
Harmonic (THD)	< 3 % (at 400V AC voltage and rated power)
Power factor at rated power / Adjustable power factor	> 0.99 / 0.8 leading - 0.8 lagging
Feed-in phases / AC connection	3 / 3 - N - PE
Backup data	
Rated voltage	3 / N / PE, 220 V / 380 V, 230 V / 400 V
Rated frequency	50 Hz / 60 Hz
THDv (@ Linear load)	< 2 % (at rated power)
Backup switch time	≤ 10 ms
Rated output power	110 kW
Peak load power	1.5 times of rated power, 10 s
Efficiency	
Max. efficiency / European efficiency	98.5 % / 98.2 %
Protection & function	
Grid monitoring	Yes
DC reverse polarity protection	Yes
AC short-circuit protection	Yes
Leakage current protection	Yes
DC switch	Yes
Ground fault monitoring	Yes
PV string current monitoring	Yes
Arc fault circuit interrupter (AFCI)	Yes
Surge protection	DC Type I+II / AC Type II
PID zero	Yes
Battery input reverse polarity protection	Yes
General data	
Topology	Transformerless
Degree of protection	IP66
Dimensions (W * H * D)	1095 mm * 795 mm * 360 mm
Weight	≤ 128 kg
Mounting method	Wall-mounting bracket
Operating ambient temperature range	-30 °C ~ 60 °C
Allowable relative humidity range (non-condensing)	0 - 100 %
Corrosion	C5
Cooling method	Smart forced air cooling
Max. operating altitude	3000 m
Noise (Typical)	≤ 65 dB (A)
Grid compliance	IEC 62109-1/-2, IEC 62477-1, IEC 62920, EN 55011, AS/NZS 4777.2:2020, EN 50549, EN 50530, IEC 61683, IEC 62116, IEC 61727, IEC 60068, IEC 61000-6-3, IEC 63027
Interface	
Display	LED, Bluetooth + APP
Communication with battery	CAN
Communication with Logger	RS485
Communication between Logger and iSolarCloud	4G / WLAN / Ethernet
DI / DO	DI * 2 / DO * 3
DC connection type	MC4 (Max. 6 mm ²)
AC connection type*****	OT / DT terminal (Max. 300 mm ²)

* Input voltage exceeding the MPPT operating voltage range triggers inverter protection

** Please refer to the user manual for the full load MPPT voltage range

*** Minimum battery voltage for black-start : 270 V

**** Depending on the connected battery

***** Please refer to the user manual for detail information

